

Pressure Supervisory Switches

These switches are operated by supervised fluid pressure applied to a built-in bellows, diaphragm or Bourdon tube which is mechanically linked to the switch member. The normal arrangement provides for the switch contacts to open automatically if the supervised pressure is reduced to a potentially unsafe point. Other equipment then acts to shut down the combustion process, as applicable. For alarm or other purposes, the switch action may be the reverse.

Switches having a means of adjusting the operating pressure range require cover removal to accomplish adjustment.

When ordering, specify type, model, maximum operating pressure, temperature, fluid handled, electrical characteristics and operating pressure desired.

Pressure Supervisory Switches for Fuel Gas and Ventilating or Combustion Air

These switches may also be used as airflow interlocking switches and are recommended for safety cock applications.

FAN 1.2, FAN 010, FAN 050, FAN 110, FAB 1.2, FAB 010, FAB 050, FAB

Air Pressure Switch Models: FAN 1.2, FAN 010, FAN 050, FAN 110, FAB 1.2, FAB 010, FAB 050, FAB 110. Switches rated 6A @ 120/240 VAC, 5°F to 180°F (-15°C to 82°C).

Gas Pressure Switch Models: FGA-L 010, FGA-L 050, FGA-L 110, FGA-L 410, FGM-L 010, FGM-L 050, FGM-L 075, FGM-L 136, FGA-H 010, FGA-H 050, FGA-H 110, FGA-H 410, FGM-H 050, FGM-H 087, FGM-H 150. Switches rated 6A @ 120/240 VAC, 5°F to 180°F (-15°C to 82°C).

Company Name:	Antunes Controls Div A J Antunes & Co
Company Address:	180 Kehoe Blvd, Carol Stream, Illinois 60188, USA
Company Website:	http://www.ajantunes.com
Listing Country:	United States of America
Certification Type:	FM Approved